

CM22 Indoor Mini Dome Camera

Essential 3MP Coverage in a Compact Form Factor



Overview

The CM22 mini dome camera provides 3MP coverage in a compact form factor and is therefore well-suited for discreet deployments and small spaces. With a 1 / 2.8" progressive CMOS image sensor and 10 meters / 33 feet of IR range, the CM22 offers reliable visibility for organizations seeking quick and scalable installations. The CM22 also includes an onboard CV25S Ambarella processor to detect and alert on the presence of people and vehicles. The CM22 excels at covering areas such as small storage closets or store aisles where space is limited or subtlety is needed.

The CM22's sleek design and durability enable organizations to deploy a tamper-resistant camera in small spaces while also keeping aesthetics top-of-mind. Installation is simple and intuitive, and setup is easy to track with an LED status indicator. The included mount plate additionally allows the camera to be mounted to a wall or ceiling without any additional hardware.

Key features

Clear image quality

- 1 / 2.8" progressive CMOS image sensor
- 3MP resolution
- 10 meters / 33 feet of IR range for nighttime viewing

Essential detection

- Onboard CV25S Ambarella processor enables people and vehicle detection

Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 90 days (256GB - 768GB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

Easy installation

- Mounting plate and screw pack included
- LED light status indicator